GRID ANTENNA 2150 - 2686 MHz

Features of the 2150 MHz Wire Grid Antenna

- True to Specification Performance - Excellent RF Performance
- Narrow beamwidth to minimize outside interference
- Lowest Windload for extreme, wind, or snow environments
- Zinc plated cold rolled steel with polyester powder coat
- Polyester powder coat L Bracket and Muffler Clamp - SS Hardware
- Heavy Duty Mounting Bracket and Double U Bolts Included
- Vertical or Horizontal Polarization for easy installation
- Passive Feed available in male or female N connector M/F
- 12” quality microwave cable with lifetime warranty N connector
- Ultrasonic weld on UV stabilized ABS plastic passive feed
- For use with 1" - 2 3/4” Diameter mast/poles (25 - 70 mm)
- -45 to +70 Degrees Centigrade Operating Temperatures
- Use for ISM, WISP, WIFi, WiMAX Networks - 802.11 Compatible
- BRS - EBS - MMDS - MDS - WCS

GA2132M/F

Shipped Direct from Manufacturer

One Year Warranty, Repair or Replacement, Provided by Manufacturer

Backhaul Point-to-Point

Customer Premises Equipment

1 Wireless Way

SPECIFICATIONS

Part Number	GA2132M or GA2132F
Frequency Range	2150 - 2686 MHz
Gain	26 dBi
Front to Back Ratio	<27 dBc
Return Loss	10 dB
Beamwidth	8.6 Degrees
VSWR	1.5:1 or less Typical
Input Impedance	50 Ohms
Maximum Power	200 Watts
Connector Interface	N Type
Windload	210 MPH
Polarization	Vertical or Horizontal
Lightning Protection	Direct Ground
L X W X H	32”X32”X11”
	812mmX812mmX279mm
Weight	10 lb/4.5 kg
Mast Sizes Compatible	1”-2.75” 25mm-70mm
Grid Antenna includes	passive feed, hardware kit
extension tube and	wire grid reflector

www.1wirelessway.com