

**GRID ANTENNA 4900, 5200, 5400, 5700 MHz**

**Backhaul Point-to-Point  
Customer Premises Equipment**

**Features of the 4.9 - 5.7 GHz Wire Grid Antenna  
with arm to mount Motorola Canopy Module**

- True to Specification Performance - Excellent RF Performance
- Narrow beamwidth to minimize outside interference
- Lowest Windload for extreme, wind, or snow environments
- Zinc plated cold rolled steel with polyester powder coat
- Polyester powder coat L Bracket and Muffler Clamp - SS Hardware
- Heavy Duty Mounting Bracket and Single U Bolt Included
- Engineered Specifically for 5 GHz Motorola Canopy Modules
- For use with 1" - 2 1/2" Diameter mast/poles (28 - 64 mm)



**SPECIFICATIONS**

- 45 to +70 Degrees Centigrade Operating Temperatures
- Use for ISM, WISP, WiFi, WiMAX Networks - 802.11 Compatible

Part Number: GAMC14R  
Frequency Range: 4900 - 5900 MHz

**GAMC14R**



Gain: 16 dBi  
Front to Back Ratio: <18 dBc  
Return Loss: 26 dB  
Beamwidth: 25H 14V Degrees  
VSWR: 1.5:1 or less Typical  
Input Impedance: 50 Ohms  
Maximum Power: 200 Watts  
Windload: 210 MPH  
Polarization: Vertical  
Lightning Protection: Direct Ground  
L X W X H: 14"X14"X3"  
356mmX356mmX76mm  
Weight: 4 lb/1.8 kg  
Mast Sizes Compatible: 1"-2.5" 28mm-64mm

Shipped Direct from Manufacturer

Grid Antenna includes hardware kit  
arm to mount module and wire grid reflector

One Year Warranty, Repair or Replacement, Provided by Manufacturer

[www.1wirelessway.com](http://www.1wirelessway.com)