

GRID ANTENNA 2400 - 2485 MHz

**Backhaul Point-to-Point
Customer Premises Equipment**

**Features of the 2400 MHz Wire Grid Antenna
with arm to mount Motorola Canopy Module**

- True to Specification Performance - Excellent RF Performance
- Narrow beamwidth to minimize outside interference
- Lowest Windload for extreme, wind, or snow environments
- Zinc plated cold rolled steel with polyester powder coat
- Polyester powder coat L Bracket and Muffler Clamp - SS Hardware
- Heavy Duty Mounting Bracket and Single U Bolt Included
- Engineered for 2.4 GHz Motorola Canopy Modules
- For use with 1" - 2 3/4" Diameter mast/poles (25 - 70 mm)



- 45 to +70 Degrees Centigrade Operating Temperatures
- Use for ISM, WISP, WiFi, WiMAX Networks - 802.11 Compatible

SPECIFICATIONS

Part Number	GAMC2415
Frequency Range	2400 - 2485 MHz
Gain	15 dBi
Front to Back Ratio	<19 dBc
Return Loss	12 dB
Beamwidth	21H 19V Degrees
VSWR	1.5:1 or less Typical
Input Impedance	50 Ohms
Maximum Power	200 Watts
Connector Interface	N Type
Windload	8 lbs or 210 MPH
Lightning Protection	Direct Ground
L X W X H	20"X16"X11"
	508mmX406mmX279mm
Weight	2 lb/0.9 kg
Mast Sizes Compatible	1"-2.75" 25mm-70mm

GAMC2415



Grid Antenna includes wire grid reflector arm and hardware kit

Shipped Direct from Manufacturer

One Year Warranty, Repair or Replacement, Provided by Manufacturer

www.1wirelessway.com