

## OMNI ANTENNA 2500 - 2686 MHz


### Features of the 2500 MHz Omni Directional Antenna

- True to Specification Performance to Minimize Outside Interference
- High Performance Design Eliminates Nulls
- Extra Strong Aluminum Construction - Waterproof
- Powder Coated Enclosure for Rough Environments
- Vertical Polarization - IEEE 802.11 Compatible
- Lifetime Warranty Female N Connector
- For use with 1.5" - 2.76" Diameter Mast/Poles/Mounts (40 - 70mm)
- 45 to +70 Degrees Centigrade Operating Temperatures
- DC Ground for Lightning Protection
- Rugged Double Clamping Hardware System SS Hardware
- Use for 2500 MHz Networks



Shipped Direct from Manufacturer

One Year Warranty, Repair or Replacement, Provided by Manufacturer

OMNI		NLOS
Base Station		None Line of Sight Applications
		
SPECIFICATIONS		
Part Number	OM2506V	
Frequency Range	2500 - 2686 MHz	
Gain	6 dBi	
VSWR	1:5:1 Typical	
Impedance	50 Ohms	
Maximum Power	100 Watts	
Beamwidth	25E	
PIM	<107	
Structure	UV Res Fiberglass	
Wind Velocity	130 mph/210 kmh	
Length	26.38"/670mm	
Weight	1.77#/0.7kg	
Mounting Hardware	S/S U Bolt with Muffler Brace	
DC Ground	Photo	may not be exact model
		<a href="http://www.1wirelessway.com">www.1wirelessway.com</a>