

OMNI ANTENNA 2500 - 2686 MHz


Features of the 2500 MHz Omni Directional Antenna

- True to Specification Performance to Minimize Outside Interference
- High Performance Design Eliminates Nulls
- Extra Strong Aluminum Construction - Waterproof
- Powder Coated Enclosure for Rough Environments
- Vertical Polarization - IEEE 802.11 Compatible
- Lifetime Warranty Female N Connector
- For use with 1.5"- 2.76" Diameter Mast/Poles/Mounts (40 - 70mm)
- 45 to +70 Degrees Centigrade Operating Temperatures
- DC Ground for Lightning Protection
- Rugged Double Clamping Hardware System SS Hardware
- Use for 2500 MHz Networks



Shipped Direct from Manufacturer

One Year Warranty, Repair or Replacement, Provided by Manufacturer

OMNI	NLOS
Base Station	None Line of Sight Applications
	
SPECIFICATIONS	
Part Number	OM2509V
Frequency Range	2500 - 2686 MHz
Gain	9 dBi
VSWR	1:5:1 Typical
Impedance	50 Ohms
Maximum Power	100 Watts
Beamwidth	14 E
PIM	<107
Structure	UV Res Fiberglass
Wind Velocity	130 mph/210 kmh
Length	35.83"/910mm
Weight	2.2#/1.05 kg
Mounting Hardware	S/S U Bolt with Muffler Brace
DC Ground	Photo may not be exact model
	www.1wirelessway.com