


## OMNI ANTENNA 5700 - 5900 MHz


### Features of the 5700 MHz Omni Directional Antenna

- True to Specification Performance to minimize outside interference
- High Performance Design Eliminates Nulls
- Extra Strong UV Resistant Fiberglass Construction - Waterproof
- Stainless Steel Base and Stainless Steel Hardware
- Horizontal Polarization - IEEE 802.11 Compatible
- Lifetime Warranty Female N Connector
- For use with 1.5" - 2.0" Diameter mast/poles (40 - 50 mm)
- 45 to +70 Degrees Centigrade Operating Temperatures
- DC Ground for Lightning Protection
- Rugged U-Bolt Mounting Hardware with Muffler Brace
- Use for 5700 MHz Networks



Shipped Direct from Manufacturer

One Year Warranty, Repair or Replacement, Provided by Manufacturer

	OMNI	NLOS
	Base Station	ACCESS POINTS
		
<b>SPECIFICATIONS</b>		
Part Number	OM5710H	
Frequency Range	5700 - 5900 MHz	
Gain	10 dBi	
VSWR	1:5:1 Typical	
Impedance	50 Ohms	
Maximum Power	150 Watts	
Beamwidth	12	
Polarization	Horizontal	
PIM (dBm)	<107	
Structure	Aluminum	
Wind Velocity	130 mph/210 kmh	
Length	29.5"/750 mm	
Weight	1.45#/0.66 kg	
Fits Mast Size	1.5"-2.0"/40-50 mm	
DC Ground	Photo	may not be exact model
		<a href="http://www.1wirelessway.com">www.1wirelessway.com</a>