

PANEL - SECTOR ANTENNA 2400 - 2483 MHz

	NLOS	None Line of Site Applications
Features of the 2400 MHz Sector Antenna	BASE STATION	APPLICATIONS
True to Specification Performance for Excellent RF Operation		
Air Dielectric Construction		
Copper Clad PCB for Radiation Elements		
Broadband Dipole Array on Aluminum Extrusion Reflector		
Irridite Treated Aluminum for Reflector		
Powder Coat Finish over Heavy Duty Aluminum		
UV Stabilized Resistant PVC Plastic Radome for Long Life		
DC Ground for Lightning Protection	SPECIFICATIONS	
Lifetime Warranty Female N Connector	Part Number	PA2412015V
Heat Shrink on Recessed Connector for Moisture Control	Frequency Range	2400 - 2483 MHz
Heavy Duty Stainless Steel Scissor Tilt Mounting System	Gain	15 dBi
Mechanical Downtilt up to 15 Degrees Adjustable	Beamwidth	120 H 7 V
-45 to +70 Degrees Centigrade Operating Temperatures	Front to Back Ratio	>=25
	VSWR	1.5 or less typical
	Rated Wind Velocity	210km/h 130m/h
	Maximum Power	100 Watts
	Polarization	Vertical
	Input Impedance	50 Ohms
	Construction	Air Dielectric
	Radiation Element	Aluminum Alloy
	Radome Material	UV Resistant PVC
	Mounting Hardware	Steel Tilt Brackets
	Connector Interface	Female N
	Structure	One Panel
	Lightning Protection	Direct Ground
	Length	40.16"/1020mm
	Width	6.3"/160mm
	Depth	3.1"/80mm
	Weight	9.7#/4.4kg
	Mast Sizes Compatible	1.5"-3.5"/40-90mm
	Mounting Brackets	Polyester Powder Coat
	Mounting Hardware	Stainless Steel Nuts & Bolts
Shipped Direct from Manufacturer	Photo may not be	exact model
One Year Warranty, Repair or Replacement, Provided by Manufacturer		www.1wirelessway.com

